

LP-2396K

LP-2396K Outdoor 2.4Ghz Wireless AP/CPE/Bridge

Features

- Wireless Standards : IEEE 802.11b/g/n
- Data transmission rate up to 300 Mbps at 40 MHz bandwidth
- Operation Mode: Bridge/Wireless ISP
- Wireless Mode: AP/Station/WDS AP/WDS Station
- Reliable data security including WEP, WPA/WPA2, WPA-PSK/RADIUS, and WPA2-PSK/RADIUS with TKIP/AES encryption.
- Support SNMP V2 management, SSH, NTP, and Telnet.
- Support QoS bandwidth control
- MAC Access Control
- Built-in Web-based management and firmware upgrade
- PoE pass through available on Secondary Ethernet port (Configurable via Web UI)
- Remotely enable system reset by PoE Injector



Specification

Wireless Solution (Chipset)

Atheros AR9344

Flash Memory / SDRAM

8MB/64MB

Interface

One 10/100Mbps Ethernet Port (Main) One

10/100Mbps Ethernet Port (Secondary)

Reset button

Earth Ground

Antenna

12 dBi Dual Polarization, Directional antenna

Data Rate

802.11b: up to 11Mbps

802.11g: up to 54Mbps

802.11n (20MHz): up to 144Mbps

802.11n (40MHz): up to 300Mbps

Channel Bandwidth

20MHz / 40MHz

Frequency Band

2.412~ 2.484GHz

Modulation

DSSS, OFDM

Media Access Control

CSMA/CA

RF Output Power

802.11b: up to 25 ± 1 dBm

802.11g: up to 22 ± 1 dBm

802.11n: up to 21 ± 1 dBm

Sensitivity

-94dBm @ 802.11b

-91dBm @ 802.11g

-89dBm @ 802.11n

Operation Temperature

-20°C ~ 70°C

Storage Temperature

-30°C ~ 80°C ambient temperature

Humidity

0 ~ 90% typical

Power Consumption

12W (Maximum)

Power Requirement

DC 24V 1A Passive PoE (Eth. cable <40m)

DC 48V 1A Passive PoE (Eth. cable <100m)

Certification

FCC, CE